



#### **Specialties for Copper and Steel/PVC Pipe**

- Hot Tapping Saddles/Sleeves/Equipment/Cutters
- Line Stopping Saddles/Sleeves/Equipment/Sealing Elements
- CO2 and LN2 Pipe Freezing Kits
- Pipe Repair Clamps for Copper, Steel, PVC ACP, DI & CI
- Deep Hole Saws and Cutters - Stock and Special Order
- Repair Couplings, Roll Groovers, Soil Pipe Cutters
- Water Rams, Drain Cleaners and more

## **THIS IS THE RECOMMENDED CARE INSTRUCTION SHEET FOR TAPMASTER™ & 3<sup>RD</sup> PARTY LINE STOP SEALING ELEMENTS**

**PLEASE UTILIZE THE FOLLOWING INFORMATION TO GET THE LONGEST DURATION  
OUT OF YOUR LEADING EDGE/SPLIT CUP LINE STOP SEALING ELEMENTS**

1. The Polyurethane LE Sealing Elements have been HEAT cured for maximum strength.
2. Never store in direct sunlight as UV rays will cause the Sealing Elements to deteriorate prematurely.
3. If stored outdoors these Sealing Elements should be covered with Dark Plastic for longest life expectancy.
4. Never store the Sealing Elements on the Line Stop Heads as that will cause premature failure.
5. Never leave the Sealing Elements folded on the Line Stop Heads except during transport and use.
6. Remove Sealing Element from the Line Stop Heads ASAP when not in use.
7. Always store inside in A COOL DRY place in your shop or warehouse.
8. Never store the Sealing Elements on Concrete Floors.
9. Clean Sealing Elements after use with warm soapy water before being stored.