



Specialties for Copper and Steel/PVC pipe

- Hot Tapping Saddles/Sleeves
- Line Stopping Saddles/Sleeves
- Pipe Freezing Kits
- Pipe Repair Clamps
- Deep Hole Saws

Brand Names You Can Trust!

PowerSeal • JCM • Jet Swet • Smith-Blair • Wheeler Rex
TapMaster • Blu-Mol • Relton • General Wire • Qwik-Freezer

Home of the Insta-Clamp™ Solder Joint Repair Clamp ½" to 4.00"

PACE Model 1112

1"-12" Sched 40 Portable Electric Drive Roll Groover



model 1112

Portable Roll Groover

Capacity: 1" through 12" pipe (25-305mm) Schedule 40
Model 1112 requires just three Top Rollers and three Bottom Rollers to produce specification quality grooves in pipe from 1" through 12" diameter Schedule 40. Easily portable for on-the-job work, the Model 1112's electric motor rotates pipe at speeds of 35 RPM. The hand hydraulic pump will deliver up to 15,000 psi pressure at the point of roll grooving. Like all PACE Pipe Grooving Machines, Model 1112 is ruggedly built to deliver long, trouble-free service.

MODEL 1112 SPECIFICATIONS

Capacity: 1" through 12" SCHED 40 (10mm)
2" through 6" Copper Tubing K,L,M and DWV

Pipe Rotation Speed: 35 RPM

Hydraulic Pressure at Roller: 15,000 psi max

Spindle Height from Floor: 35" (889mm)

Electric Motor: 1 1/2 HP 60Hz 110 V.1 PH.*

Floor Space Required: 32" x 32" (813x813 mm)

Shipping Weight: 220 lbs. (100kg)

Interchangeable Rollers:

TOP PIPE DIAMETER

1" through 1 1/2" (25-38mm)

2" through 6" (51-152mm)

8" through 12" (203-305mm)

*Other current characteristics available

BOTTOM PIPE DIAMETER

1" through 1 1/2" (25-38mm)

2" through 6" (51-152mm)

8" through 12" (203-305mm)

STANDARD EQUIPMENT

Electric Drive Motor • Groove Depth Gauge • Hydraulic Hand Pump • Top and Bottom Rollers 1-12" • Shipping/Storage Box • Guards • Foot Switch

OPTIONAL: Top and Bottom Copper Rollers 2-8"; Nipple Bracket